


Heat gun 2000W 2 stages regulatin 2000W RD-HG12

Art. number: **122105**

Barcode: **3800123143885**

- ✓ Ergonomic handle
- ✓ 2 stages
- ✓ Temperature control
- ✓ Convenient storage case



TECHNICAL FEATURES

| Parameter | Measure Unit | Value |
|---|--------------|--------------------------|
| Air flow work rate at at stage i (l/min) | l/min | 240 |
| Air flow work rate at at stage ii (l/min) | l/min | 480 |
| Cable length (m) | m | 2 |
| Maximum delivery rate (l/min) | l/min | 480 |
| Rated input power (W) | W | 2000 |
| Rated voltage (V) | V | 230 |
| Number of air volume levels | | 2 |
| Number of air temperature levels | | 2 |
| Output nozzle temperature @ stage i (°C) | °C | 80 |
| Output nozzle temperature @ stage ii (°C) | °C | 600 |
| Rated voltage type | | Corded - Electrical Grid |

EQUIPMENT

| | |
|--------------------|-------|
| Wide Nozzle | 2pcs. |
| Reducing Nozzle | 1 pc. |
| Reflector Nozzle | 1 pc. |
| Triangular scraper | 1 pc. |
| Tool case | 1 pc. |

LOGISTICS INFORMATION

| Type of package | Quantity | Width Length Height | Volume | Net Brutto Tara | Barcode |
|-----------------|----------|---------------------------|------------|-------------------------------|----------------|
| pieces | 1 pieces | 28 x 9 x 28 cm | 0.00706 m3 | 1.8000 - 2.0000 - 0.2000 kg | 3800123143885 |
| carton | 5 pieces | 31 x 47 x 31 cm | 0.04517 m3 | 10.0000 - 10.0000 - 0.0000 kg | 38001231438856 |