

Welding Helmet auto-darkening DIN 9-13 Grinding RD-WH02

Art. number: **138302**

Barcode: **3800123174285**

- ✓ Dimming control
- ✓ Fully automatic on and off
- ✓ Photosolar + Lithium-ion battery power supply



TECHNICAL FEATURES

Parameter	Measure Unit	Value
Uv/ir protection (DIN)	DIN	16
Light to dark adaptation time (sec)	sec	0.2 - 1.0
Material		PP
Operating temperature (°C)	°C	-10 - 55
Packing (pcs.)	pcs	1
Sensor		2
Dark shade state (DIN)	DIN	9-13
Storage temperature (°C)	°C	-20 - 70
Rated voltage type		Solar Cells + Li-Ion Battery
In accordance with		CE EN175 EN379
Turing on & off		Automatically
Switching time (sec)	sec	1/25000
Tig range (amps/DC; amps/AC)	amps/DC; amps/AC	≥ 35; ≥ 15
Optical class		1/1/1/2
Light shade state (DIN)	DIN	4
View size (mm)	mm	92x42
View size (mm)	mm	108.5x89.5
Filter dimensions (mm)	mm	110x90x9
Sensitivity control		Outer Side Smooth Adjustment From Low To High

LOGISTICS INFORMATION

Type of package	Quantity	Width Length Height	Volume	Net Brutto Tara	Barcode
pieces	1 pieces	24 x 31 x 24 cm	0.01786 m3	0.2500 - 0.2717 - 0.0217 kg	3800123174285
carton	6 pieces	49 x 72 x 32 cm	0.11290 m3	1.6300 - 1.6300 - 0.0000 kg	38001231742854