

## Welding Helmet auto-darkening DIN 9-13 Gr 100x50 RD-WH08

## Art. number: **138348** Barcode: **3800972030855**

✓ The photo-solar filter automatically darkens when welding starts and brightens when the process is finished ✓ Protection class DIN 9-13 provides reliable protection against harmful UV and IR rays, protecting eyes and face from burns and injuries ✓ The ability to adjust the dimming level allows the helmet to be customized according to specific needs ✓ Made of highly resistant polymer, the helmet is durable and resistant to mechanical damage





 ✓ Suitable for various types of welding operations such as
MIG, TIG, MMA, etc.

## TECHNICAL FEATURES

| Parameter                           | Measure Unit                                  | Value                        |  |
|-------------------------------------|---|------------------------------|--|
| Uv/ir protection (DIN)              | DIN   | 16                           |  |
| Light to dark adaptation time (sec) | sec   | 0.1 - 1.0                    |  |
| Material                            |   | РР                           |  |
| Operating temperature (°C)          | °C  |                              |  |
| Packing (pcs.)                      | pcs   | 1                            |  |
| Sensor                              |   | 4                            |  |
| Dark shade state (DIN)              | DIN   | 5-13                         |  |
| Storage temperature (°C)            | °C  |                              |  |
| Rated voltage type                  |   | Solar Cells + Li-Ion Battery |  |
| Turing on & off                     |   | Automatically                |  |
| Switching time (sec)                | sec   | -                            |  |
| Tig range (amps/DC; amps/AC)        | amps/DC; amps/AC                              | 5                            |  |
| Optical class                       |   | 1/1/1/2                      |  |
| Light shade state (DIN)             | DIN   | 4                            |  |
| View size (mm)                      | mm  | 100x50                       |  |
| Filter dimensions (mm)              | mm  | 125x102x18                   |  |
| Sensitivity control                 | Outer Side Smooth Adjustment From Low To High |                              |  |

| LOGISTICS INFORMATION |          |                   |            |                             |                |
|-----------------------|----------|-------------------|------------|-----------------------------|----------------|
| Type of package       | Quantity | Width<br>Length   | Volume     | Net<br>Brutto               | Barcode        |
|                       |          | Height            |            | Tara                        |                |
| pieces                | 1 pieces | 23.5 x 27 x 27 cm | 0.01713 m3 | 0.7000 - 0.8833 - 0.1833 kg | 3800972030855  |
| carton                | 6 pieces | 29 x 73.5 x 56 cm | 0.11936 m3 | 5.3000 - 5.3000 - 0.0000 kg | 38009720308550 |